

Ascom d62 DECT Handset, Talker

Features

- GAP/CAP compliant DECT handset
- Dynamic output power
- High quality voice
- Colour display
- Cleanable, IP 44
- Local, central, and company phonebook¹
- 18 Languages and 1 customizable
- Broadcast/Multicast messaging
- Mini messaging (12 characters)
- Voice mail
- Loudspeaking function
- Multifunction button
- Mute button/Sound off key
- Manual and automatic keypad lock
- 3 programmable soft keys
- 9 programmable hot keys
- Customized GUI
- Profiles
- Clear lists in charger
- Call list with the 25 last calls
- Easy access to PBX services
- Vibrator
- Easy replacement
- Easy replaceable battery
- Centralized management
- Standard headset connector 2.5 mm
- Site Survey tool
- Bluetooth as option
- Upgradeable with licences



Technical Specifications

Physical

Dimensions (l x w x d):	134 x 53 x 26 mm
Weight:	130 g (battery and clip included)
Material:	Case: PC-ABS, Key pad: PC, Clip: PPA
Colour:	Steel grey
Display (w x h):	28 x 35 mm, CSTN display
Clip:	Hinge-type (standard) or swivel-type

Battery

Type:	Li-polymer
Speech time:	20 h
Stand-by time:	240 h ²
Speech time with Bluetooth option:	13 h with Bluetooth headset in use 20 h without Bluetooth headset in use
Stand-by time with Bluetooth option:	120 h ²
Charge time:	< 4 hours
Discharge/charge cycles:	>=80% capacity left after 400 full charge/discharge cycle.

1. Central phonebook is a system dependent feature.

2. The stand-by time is without activated screensaver.

Connectors

Multi-purpose connector:	For battery charging, software download, and configuration
Headset connector:	Standard 2.5 mm

User interface

Display (w × h):	Multiple colours with high resolution, more than 65000 individual colours. 128 × 160 pixel LCD with white LED backlighting.
Indicator:	LED on top/front for visual indication of incoming call/message. The LED may also be used for visual indication of normal function.
Vibrator:	Incoming call/message
Buttons/Keypad:	<ul style="list-style-type: none">- Soft keys (3)- Hook off key- On hook and Power On/Off on the same key- Five way navigation key (OK button in the centre of the key)- Numerical keys- Sound off key- Volume up/down keys- Multifunction button- Mute button

Audio

Ring signal:	Adjustable in 8 steps
Earpiece:	Adjustable in 8 steps of 3dB each
Maximum sound ring signal level:	88 dBA @ 10 cm
Loudspeaker:	Duplex loudspeaking function

Settings

Languages:	18 (Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese (Brazilian), Russian, Slovakian, Spanish, Swedish, and Turkish), + 1 downloadable.
------------	---

Central Phonebook

Maximum name and number length:	40 characters in a name and 20 digits in a number
---------------------------------	---

Company Phonebook

Maximum name and number length:	24 characters in a name and 24 digits in a number (1 number per name).
Entries:	1000

Local Phonebook

Storage of contacts:	<ul style="list-style-type: none">- 48 character name- 24 digit work number- 24 digit mobile phone number- 24 digit other number- Selectable ring tones per contact
Entries:	250

Telephony

Indication:	14 ring signals, flashing LED and vibrator
Answer call:	Button press or auto answer

Specifications are subject to change without notice.

Call list storage capacity: 25 calls (received, dialled and missed) with time stamp

Messaging

Maximum message length: 12 to Handset

Storage capacity: 0

Radio

Receiver sensitivity: -93 dBm

Automatic DECT protocol detection: Automatic detection and configuration for US DECT and EU DECT at first registration.

Frequency range:

- EU: 1880-1900 MHz
- US: 1920-1930 MHz
- LA: 1910-1930 MHz
- BR: 1910-1920 MHz
- -- : 1900-1920 MHz

Modulation: GFSK

Channel spacing: 1.728 MHz

Antenna: Integral

Sensitivity: -93 dBm

Radiated power: EU: 250 mW
US: 100 mW

Environmental

Operating temperature: 0°C to +40°C

Storage temperature:³ -20°C to +60°C

Enclosure protection: IP44, IEC EN60529

Immunity to electromagnetic fields: 3V/m EN61000-4-3

Immunity to ESD: 4 kV contact discharge and 8 kV air discharge (EN61000-4-2)

Free fall test, standard product: IEC 60068-2-32, procedure 1, dropped 12 times from 1 metre.
Ascom approves 12 drops from 1.5 metre.

Option

Bluetooth radio: Add-on from factory

Radio spectrum: ISM 2.4000-2.4835 MHz


Accessories

- Leather case
- Hinge type/Swivel type clip
- Security cord
- Desktop charger, Basic
- Desktop charger, Advanced
- Charging Rack
- Separate battery pack charger
- Headset with microphone on cable, DTX-9016
- Headset with microphone on boom, DTX-9017
- Bluetooth Headset (10 supported)
 - SonyEricsson HBH-PV702
 - SonyEricsson HBH-GV435
 - SonyEricsson HBH-IV835
 - Plantronics Voyager510
 - Plantronics Explorer665
 - Nokia BH-201
 - Jabra BT8010
 - Motorola H350
 - Motorola H670
 - Samsung WEP410


3. Note that storing Li-polymer batteries at high temperature dramatically reduces its capacity. For example storage around maximum temperature reduces capacity with 20% in less than a month, permanently.

Specifications are subject to change without notice.


Compliance to European regulations and standards

EU directives:	1999/5/EC (R&TTE)
Product marking:	CE  BT ID: B014317
Radio:	EN 301 406, TBR22
Bluetooth:	EN 300 328-2, EN 301489-17
SAR (Specific Absorption Rate):	EN50360 and EN62209-1, 0.074 W/kg (10 gram)
Safety:	EN60950-1
EMC:	EN301489- 6, EN 301 489-1



Compliance to US regulations and standards

Product marking:	FCC ID: BXZDH4 US: 9FVW4NANDH4 HAC
Bluetooth:	FCC ID:BXZDH4BL,  BT ID: B014317
SAR (Specific Absorption Rate):	FCC/OET Bulletin 65 Supplement C and IEEE Std. 1528 / ANSI/IEEE Std. C95.1 Normal operation 0.104 W/kg (1 gram) Body worn operation 0.029 W/kg (1 gram)
Safety:	UL 60950-1
EMC/Radio:	FCC Part 15 D, and FCC Part 15 C (Bluetooth)
Hearing Aid:	47 CFR Part 68, Subpart D and TIA-968-A

Compliance to Canadian regulations and standards

Product marking:	IC:3724B-DH4
Bluetooth:	IC: 3724B-DH4BL,  BT ID: B014317
EMC/Radio:	RSS-213 and RSS-210 (Bluetooth), ICES-003
SAR (Specific Absorption Rate):	IEEE Std C95.1 Normal operation 0.104 W/kg (1 gram) Body worn operation 0.029 W/kg (1 gram)
Safety:	CSA 60950-1
Hearing aid:	CS-03

Compliance to Australian regulations and standards

Product marking:	  BT ID: B014317
Radio:	EN301406
Bluetooth:	EN 300 328-2, EN 301489-17, AUS/NZS-4771
SAR (Specific Absorption Rate):	EN 50360 and EN62209-1, 0.074 W/kg (10 gram)
Safety:	AUS/NZS 60950-1
EMC:	EN301489- 6, EN 301 489-1
DECT:	AS/ACIF 5004, TS028

Specifications are subject to change without notice.