

Dialog 3310 ISDN Telephone

The Dialog 3310 is a fully featured digital phone for both business and home users.

The Dialog 3310 has a menu-driven user-friendly set-up that provides rapid access to ISDN services. Simple programming makes the phone quick to install and easy to use. It connects to the ISDN network via the S0 interface, in addition to being Euro-ISDN compatible.

Dialog 3310 has the appreciated Dialog 3000 design that integrates seamlessly into the MD110 installations with Dialog 3200 and 3100. Dialog 3310 is not only stylish, but ergonomically sound as well. The 2 x 20 alphanumeric LCD display is tiltable at four angles and shows the time, date, menu and the called party's number



Telephone features

- Simultaneous voice and data communication
- 2 x 20 alphanumeric character display showing time, date, menu and the called party's number
- 20 function keys, of which 5 are menu keys, 9 are dial-by-name keys, 5 have fixed functions and one is a redial key
- Volume control for handset receiver and loud speaker
- Programmable ringer level and tone
- Mute key with LED indicator to disconnect microphone
- Scrolling function
- 9 dial-by-name keys that can be labeled by the user
- Call duration display
- Multiple subscriber number with LED indicator and ring tone
- Programming lock with 5-digit PIN code
- Retrieval and redial of the last three numbers dialed
- Toggle between two calls
- English, German or French user menu
- Phone book to store up to 50 memory location with name and phone number
- Room monitoring (babysitting) function
- Do-not-disturb function (phone silent)

- Up/down select functions according to the menu
- Call blocking (partial/global)+
- Listen-in while connection is established, monitor loudspeaker
- Idle mode display messages
- Inquiry call
- Time and date setting
- Loudspeaker
- DTMF dialing/KEYPAD sending selectable

ISDN Services

- Display of calling party's number (CLIP) and name (if listed)
- Calling line identification restriction (CLIR)
- Call rejection with number storage
- Three multiple-subscriber numbers (MSN)
- Call-waiting (CW)
- Advice of charge (AOC)
- Call hold/retrieve
- Three-party service (3PTY)
- Call forwarding:
 - Unconditional (CFU):* all calls forwarded
 - Busy (CFB):* calls forwarded only when the line is busy
 - No reply (CFNR):* calls forwarded when there is no answer
- Terminal portability (TP)
- Automatic time and date
- Supports point to multi-point



Technical data

Permanent memory storage until changed by user

Restricted power, single terminal mode switch

Dimensions and weight
225 x 195 x 85 mm 915g

Color Light gray

Microphones Electret

Receiver Dynamic

Loudspeaker Dynamic

Tone ringer 9 levels and 8 tones

Transmission
Handset mode
SLR: 7 ±3,5 dB
RLR: 3 ±3,5 dB

Volume control:
-12 dB to +10 dB

Signaling
EURO-ISDN

Environmental Ranges
Operation +5 to +40°C
Storage -20 to +70°C

Please note that many features are system-dependent.